

TS-210

HIGH PERFORMANCE 1D / 2D HANDHELD SCANNER



SPECIAL FEATURES

Hochleistungs-Imaging-Technologie zum Lesen von 1D- und 2D-Barcodes
Scannen von Papieretiketten oder mobilen Geräten
Weites Scanfeld und omnidirektionale Scanfunktion
Solides Design für hohe Zuverlässigkeit und Langlebigkeit
Lautsprecher und blau / grüne LED für einfaches Bedienen

OPTIONAL

RS232 cable with 5V adaptor
Stand

TS-210

ITEM	TS-210		
Dimensions	62.8 mm (W) x 153 mm (D) x 90 mm (H)		
Weight	132 g (without cable)		
Input Voltage	5V ± 0.25 VDC		
Power Requirement	Scanning: 300 mA (Max: 480 mA) Standby: 160 mA		
Interface	RS-232, USB Keyboard, USB virtual COM		
Environment	Temperature	Operating 0°C ~ 50°C	Storage -40°C ~ 60°C
	Humidity	5% ~ 95%	5% ~ 95%
Drop Resistance	Drop Resistance		
IP-Class	IP52		
Barcode Types	1D: PC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/Plessey, UK/Plessey, China Post, China Finance, Telepen, GS1 DataBar (formerly RSS) variants		
	2D: PDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, MicroQR Code, MicroPDF417		
Image Size	1280 x 800 pixel		
Reading Indicator	Beeper, LED		
Scanning Angle	± 70°, ± 75°, ± 360° (skew, pitch, roll)		
Depth of Field	High Density series (HD)		Standard Range series (SR)
	3 mil Code39 (3 chars)	25 mm - 50 mm	/
	4 mil Code39 (9 chars)	10 mm - 90 mm	30 mm - 90 mm
	5 mil Code39 (3 chars)	5 mm - 115 mm	20 mm - 120 mm
	13 mil UPC (6 chars)	0 mm - 250 mm	0 mm - 280 mm
	20 mil Code39 (1 char)	15 mm - 340 mm	15 mm - 430 mm
	6.7 mil PDF417 (20 chars)	10 mm - 100 mm	15 mm - 120 mm
	10 mil QR (20 chars)	0 mm - 155 mm	0 mm - 165 mm
	10 mil DM (20 chars)	0 mm - 160 mm	0 mm - 165 mm
	20 mil QR (20 chars)	0 mm - 270 mm	0 mm - 340 mm

TS-210

ITEM	TS-210
Light Source	Illumination : 5000 K , white LED Aiming: 525 nm peak wavelength, green LED
Cable	2m straight, RJ45, field replaceable
Certification	CE, LVD, IP52
Optional Accessories	RS232 cable with 5V adaptor, Stand
Color	Black Gray

*Specification is subject of change without prior notice. July19

