

sewoo

Board on the economic class being served with a great performance.

LK-P25II



- Economic but, excellent performance
- Ultra Compact and Lightweight
- Large Battery Capacity
- Wide Compatibility
- USB-C Type Charging Port
- S-MDM (Sewoo MDM) supported



Bluetooth



Barcode



Portable



Durable



Drop Resistant



Easy Loading



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 3.1ips (80mm/sec)

Print Width

Up to 1.8" (48mm)

Resolution

203 dpi (8dots/mm)

Memory

8MB(Max 64MB),SRAM 8MB

Battery Voltage / Capacity

3.6V 3250mAh Li-ion

4Hrs Charging time(Charger)

6 Hrs Charging time(USB)

Standby Time

63 Hrs

Sensor

Paper end, Cover open,

Black mark

Reliability

TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

3.1" × 1.74" × 4.06"
(79 × 44.4 × 103.2mm)

Weight

190g



INTERFACES

Standard

USB C Type, Bluetooth Smart Ready
(Bluetooth4.2+BLE), NFC Tag



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, Mfi,
UKCA,BCS



OPERATING CHARACTERISTICS

Operating Temperature

14 ~ 122°F(-10 ~ 50°C)

Operating Humidity

10 ~ 80%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%

Drop Rating

5ft/1.5m (set only) to concrete

6ft/1.8m with case to concrete

Dust-and Water-resistance Rating

IP42 (With Case - TBD)



BARCODES

1D

EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
LUPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, UPC-A etc

2D

QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations

ESC/POS, CPCL, ZPL
Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Window CE & Mobile Driver & SDK

(CE 4.2~, Mobile 5.0~), Linux Driver,

Mac Driver, OPOS Driver,

JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type

Thermal paper

Media Width

2.2" (58mm)

Media Core Diameter

0.4" (12.5mm ± 0.5mm)

Media Roll Diameter

1.5" (40mm)

Thickness

0.06mm



FONTS / GRAPHICS

Character Type

FontA(12x24), FontB(9x17), Asian Font
(KOR, JPN, CHN_GB2312, CHN_BIG5),
Font0/1/2/4/5/6/7, Resident TTF,
Downloadable TTF, FontA~H, FontGS,
Resident TTF(Font0), Font1~8

Characters per Line (CPL)

Font A(12x24): 32cpl,

Font B(9x17): 42cpl,

Character Set

95 Alphanumeric,

14 International,

128 x 18 Graphic



ACCESSORIES

Standard

Thermal Roll Paper,

Belt Clip & Battery Cover

AC/DC Adapter 5VDC

Optional

Carrying Case (with Belt Clip),

Shoulder Strap, IP54 Case

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

