

sewoo

Compact size and Enhanced usability

SLK-TS400



- Structure for easy maintenance
- Design for enhanced usability
- Compact footprint to help easily fit on the counter.
- Ideal for front exit printing with Wall mount.
- Supports flexible printing exit way Front exit or top exit.
- Ideal for kitchen/bar printer with melody box(Kitchen buzzer)
- Easy handling the jam of the paper with same cover opening/closing direction as paper cutting direction.



Rugged Design



Drop Resistant



Barcode



Durable



Paper Width



Easy Loading



High Speed



Compact Design



Easy Maintenance



Various interface



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 8.6ips(220mm/sec)

Print Width

Up to 2.8" (72mm)

Resolution

180 dpi

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Paper end, Cover open

Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 1.5 Million cuts

Drawer port

2 circuits(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

5.1"×5.5"×6.0"
(130×140×154mm)

Weight

2.7lb(1.25Kg)



INTERFACES

Standard

USB(B type)+Serial
(RS-232C_25pin)Built-in,
USB(B type)+Ethernet Built-in

Optional

Wi-Fi(802.11a/b/g/n),
Bluetooth Ver 4.2(Bluegiga,iOS)



CERTIFICATIONS

CE, FCC, KC, UL/cUL, CB,
ENERGY STAR, TELEC



OPERATING CHARACTERISTICS

Operating Temperature

32 ~ 113°F(0 ~ 45°C)

Operating Humidity

35 ~ 80%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Media Width

3.14"(80mm)

Media Core Diameter

0.4"(12.5mm)

Media Roll Diameter

3.1"(ø 83mm)

Thickness

0.06~0.09mm



SOFTWARE

Emulations

ESC/POS

Drivers

Windows Driver(XP ~, Server2003 ~),
Windows CE & Mobile Driver (CE 4.2 ~,
Mobile 5.0 ~), Linux Driver, Mac Driver,
OPOS Driver, JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK, Windows SDK,
Windows CE SDK, Linux SDK



BARCODES

1D

EAN-8, EAN-13, Code 39, Code 93,
Code 128, ITF, UPC-A, UPC-E, Codabar

2D

PDF 417, QR code, DATA MATRIX



FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),
Chinese(Traditional/Simplified, 24x24),
Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

Character set

95 Alphanumeric,
14 International,
128 x 18 Graphic



ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Option

Melody Box

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuahtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

